

PRODUCT	MODEL	RETICLE	SKU#
TALOS HMR RIFLESCOPE	6-24x50 SFP	APRS-H2 SFP IR MIL	215022

IDEAL APPLICATION



TOP FEATURES

NITROGEN PURGED

Paired with a completely sealed chassis, nitrogen gas is used to purge air from the optic to help maintain internal fog-proof and waterproof capabilities.

FULLY MULTI-COATED

Athlon Optics fully multi-coated glass gives you better light transmission with optimum brightness and true color across the entire light spectrum.

WATERPROOF

Regardless of how heavy the rain is coming down or an accidental drop in the water, this sealed and gas-purged optic will remain waterproof.

ALL FEATURES


FULLY MULTI-COATED LENSES
NITROGEN PURGED
AIRCRAFT GRADE ALUMINUM TUBE
ILLUMINATED RETICLE
ETCHED GLASS RETICLE
WATERPROOF
FOG PROOF
SHOCKPROOF
ONE PIECE TUBE CONSTRUCTION

SPECS

Power	6-24X
Obj. Lens	50 mm
Tube Size	30 mm
Turrets	Capped
Eye Relief	3.75" - 3.9"
FoV @100Y	19.9 - 4.9 ft
Click Value	0.1 MIL
Adjustment Per Rotation	6 MIL
Total Elevation Adjustment	18 MIL
Total Windage Adjustment	18 MIL
Parallax Adjustment	Side Focus 10yds - ∞
Purging Material	Nitrogen
Weight	22 oz

DIMENSIONS

L1	L2	L3	L4	L5	L6	D1	D2
14.5"	4.6"	5.9"	3.9"	2.3"	2.3"	1.7"	2.3"



**SHARP, TIGHT
AND PRICED
JUST RIGHT!**